

BRCS750N15SHDP

Rev.A Jun.-2025

描述 / Descriptions

N 沟道 TO-252 塑封封装场效应管。
N-CHANNEL MOSFET in a TO-252 Plastic Package.


特征 / Features

$V_{DS}(V) = 150V$ $I_D=20.5A$
 $R_{DS(ON)}@10V \leq 75m\Omega$ (Typ. 65m Ω)
 $R_{DS(ON)}@6V \leq 120m\Omega$ (Typ. 79m Ω)
 无卤产品。HF Product.


用途 / Applications

LED 背光，非常适合高频开关和同步整流。
LED backlighting, Ideal for high-frequency switching and synchronous rectification.

内部等效电路 / Equivalent Circuit



引脚排列 / Pinning



PIN1 : G

PIN 2 : D

PIN 3 : S

PIN 4 : D

印章代码 / Marking

见印章说明。
See Marking Instructions.

极限参数 / Absolute Maximum Ratings(Ta=25°C)

参数 Parameter	符号 Symbol	数值 Rating	单位 Unit
Drain-Source Voltage	V _{DSS}	150	V
Drain Current	I _D (Tc=25°C)	20.5	A
Peak Drain Current	I _{DM}	68	A
Gate-Source Voltage	V _{GSS}	±20	V
Single Pulsed Avalanche Energy	E _{AS}	67	mJ
Avalanche Current	I _{AS}	13.4	A
Total Power Dissipation	P _D (Tc=25°C)	70	W
Junction and Storage Temperature Range	T _J , T _{STG}	-55 to 150	°C
Thermal Resistance-Junction to Ambient	R _{θJA}	75	°C/W
Thermal Resistance-Junction to Case	R _{θJC}	1.8	

电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V I _D =250μA	150	167		V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =150V V _{GS} =0V			1	μA
Gate-Body leakage current	I _{GSS}	V _{GS} =±20V V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} I _D =250μA	2	3	4	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} =10V I _D =15A		65	75	mΩ
		V _{GS} =6V I _D =10A		79	120	
Diode Forward Voltage	V _{SD}	I _S =1A V _{GS} =0V			1.2	V
Input Capacitance	C _{iss}	V _{GS} =0V V _{DS} =25V, f=1.0MHz		390		pF
Output Capacitance	C _{oss}			235		
Reverse Transfer Capacitance	C _{rss}			12		
Gate resistance	R _g	V _{GS} =0V V _{DS} =0V, f=1MHz		1.9		Ω
Total Gate Charge	Q _{g(10V)}	V _{GS} =10V V _{DS} =75V I _D =10A		5.2		nC
Total Gate Charge	Q _{g(6V)}			2.9		
Gate Source Charge	Q _{gs}			1.1		
Gate Drain Charge	Q _{gd}			1.4		

电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Turn-On DelayTime	$t_{D(on)}$	$V_{DS}=75V$ $I_D=10A$ $V_{GS}=10V$ $R_G=3\Omega$		5.7		ns
Turn-On Rise Time	t_r			2.9		
Turn-Off DelayTime	$t_{D(off)}$			6.9		
Turn-Off Fall Time	t_f			3.3		

电参数曲线图 / Electrical Characteristic Curve




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

电参数曲线图 / Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area





Figure 10: Normalized Maximum Transient Thermal Impedance

外形尺寸图 / Package Dimensions




单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	2.20	2.40	E	5.95	6.25
B	0.95	1.25	e1	2.24	2.34
b	0.70	0.90	e2	4.43	4.73
b1	0.45	0.55	L1	9.85	10.35
C	0.45	0.55	L2	1.70	2.00
D	6.45	6.75	L3	0.60	0.90
D1	5.10	5.50	K	0.00	0.10

TO-252

印章说明 / Marking Instructions



说明：

BR： 为公司代码

750N15SH： 为型号代码

****： 为生产批号代码，随生产批号变化


Note:

BR: Company Code

750N15SH: Product Type Code

****: Lot No. Code, code change with Lot No.

回流焊温度曲线图(无铅) / Temperature Profile for IR Reflow Soldering(Pb-Free)



说明：

- 1、预热温度 150~180°C，时间 60~90sec;
- 2、峰值温度 245±5°C，时间持续为 5±0.5sec;
- 3、焊接制程冷却速度为 2~10°C/sec.

Note:

- 1.Preheating:150~180°C, Time:60~90sec.
- 2.Peak Temp.:245±5°C, Duration:5±0.5sec.
3. Cooling Speed: 2~10°C/sec.

耐焊接热试验条件 / Resistance to Soldering Heat Test Conditions

温度：260±5°C

时间：10±1 sec.

Temp.:260±5°C

Time:10±1 sec

包装规格 / Packaging SPEC.

卷盘包装 / REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-252	2,500	2	5,000	6	30,000	13" ×16	360×360×50	380×335×366

套管包装 / TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

使用说明 / Notices